

User Provider

The User Provider tab allows you to configure the user providers if you want to use user synchronization with other systems.

Like in the [Source Configurations](#), you can choose between a database table and a LDAP system as source for the synchronization process.

Overview

System Settings

General Exceptions Data tests Notifications Source configurations User provider Group provider Authentication Mail

User provider

Here you can configure the user providers if you want to use user synchronization. Possible Sources for users are a database table or an LDAP system. These can be configured in the Source configuration.

1 LDAP USER PROVIDER Execute all Add

Catalis AD User Provider

2 DATABASE USER PROVIDER Add

3 **PROVIDER CONFIGURATION**

4 Name
Catalis AD User Provider

Username attribute
sAMAccountName

Language attribute

First name attribute
givenName

Last name attribute
sn

Email attribute
mail

Currency attribute

5 Hours delay
1

☒ Active

6 User search query (empty for default)
objectcategory=person

7 LDAP source
CORP

8 Details Test Save

Here you can configure the LDAP or database sources that define the user synchronization.

1. LDAP sources: list of connected LDAP sources. LDAP sources are used to manage user and group permissions. Click on 'Execute all' to synchronize your users and on 'Add' to add a new source.
2. Database sources: list of connected database sources.
3. Name: define your source name.
4. Attributes: here you can define the format of the attributes contained in your sources, such as username, language, first and last names, email and currency.
5. Hours delay: delay between synchronization attempts. Mark the 'Active' box to activate automatic synchronizations.
6. User search query: query to search for users.
7. LDAP source: defines the LDAP source from the list defined in the [Source Configurations](#).
8. Config buttons: after you are done, click on 'Save' to save your source. The 'Test' button will evaluate the connection status.